

BRADY B-8222 DIGITALLY PRINTED TYRE TREAD LABEL

TDS No. B-8222
Effective Date: 08/11/2014

Description:

GENERAL

Print Technology: Digital printing

Materials Type: Top-coated polypropylene label stock with polyester over lamination

Finish: Glossy, White

Adhesive: Permanent rubber

APPLICATIONS

Tire tread label

COMPLIANCE

RoHS 2 compliant

Details:

PHYSICAL PROPERTIES	TEST METHOD	TYPICAL RESULTS
Thickness	ASTM D1000 Substrate + Adhesive • Total	0.143mm (5.7mil)
Peel Adhesion to: • Stainless Steel • Polyethylene (HDPE) • Vulcanized rubber (Smooth) • Vulcanized rubber (Textured)	ASTM D1000 20 minute dwell 24 hour dwell 20 minute dwell 24 hour dwell 20 minute dwell 24 hour dwell 20 minute dwell 24 hour dwell	114 oz/in 116 oz/in 95 oz/in 95 oz/in 68 oz/in 73 oz/in 47 oz/in 41 oz/in
Tack (Loop) to: • Stainless Steel • HDPE • Vulcanized rubber (Smooth) • Vulcanized rubber (Textured)	ASTM D6195	3343 g 2407 g 485 g 738 g
Abrasion Resistance	Method 5306 of U.S Federal Test Method Std. No 191A CS10 grinding wheels, 250g load	Legibility remained after 100 cycles
Gloss Test	20 Degree	83 GU
Water Immersion Test	15 minutes immersion and 10 times rubbing	No visible effect

Performance properties tested on B-8222 were printed with digital printing using HP Indigo printer. Printed samples were laminated to stainless steel, HDPE, rubber (smooth and texture) surface and allowed to dwell 24 hours before exposure to the indicated environment.

PROPERTIES	TEST METHOD	TYPICAL RESULTS
------------	-------------	-----------------

High Service Temperature Resistance	50°C 1000hours exposure in oven	Slight yellowing. Print remained legible and label remained functional
Low Service Temperature Resistance	-40 °C 1000hours exposure in freezer	Print remained legible and label remained functional
Humidity Resistance	45 °C/95%RH 1000hours exposure in humidity chamber	Slight yellowing. Print remained legible and label remained functional

Product testing, customer feedback, and history of similar products, support a customer performance expectation of **at least one year from the date of receipt** for this product as long as this product is stored in its original packaging in an environment *below 80 degrees F and 60% RH*. We are confident that our product will perform well beyond this time frame. However, it remains the responsibility of the user to assess the risk of using such product. We encourage customers to develop functional testing protocols that will qualify a product's fitness for use, in their actual applications.

Trademarks and References:

ASTM: American Society for Testing and Materials (U.S.A.)

All S.I. Units (metric) are mathematically derived from the U.S. Conventional Units

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. **This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.**

Copyright 2006 Brady Worldwide, Inc., All Rights Reserved

Material may not be reproduced or distributed in any form without permission.

Trademarks:

ASTM: American Society for Testing and Materials (U.S.A.)

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Corporation Asia Pte. Ltd. | All Rights Reserved

Material may not be reproduced or distributed in any form without written permission.

