

BRADY B-919 STAINLESS STEEL VALVE TAG

TDS No. B-919
Effective Date: 04/22/2008

Description:
Stainless Steel Valve Tag for harsh environments.

Details:

Use:
Brady B-919 Stainless Steel Tags are used for general purpose valve identification.

Substrate Type:
Stainless Steel

Thickness (PSTC-33):
Total: 0.024 in. (0.609 mm)

Service Temperature:
-40°F to 1500°F (-40°C to 816°C)

Average Outdoor Durability:
5-7 years (Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques, and material color).

Chemical Resistance:

REAGENT	7 DAY IMMERSION	DIP TEST
30% Sulfuric Acid	F	F
10% Sulfuric Acid	F	F
30% HCl	F	F
10% HCl	F	F
Glacial Acetic Acid	F	F
5% Acetic Acid	F	F
50% NaOH	F	F
10% NaOH	F	F
10% Ammonia	F	F
5% Sodium Hypochlorite	F	F
10% Sodium Chloride	F	F
Methyl Ethyl Ketone	NE	NE
Acetone	NE	NE
Toluene	NE	NE
Methanol	NE	NE
IPA (Isopropanol)	NE	NE
Heptane	NE	NE
Mineral Spirits	NE	NE
Turpentine	NE	NE
Diesel Fuel	NE	NE
Kerosene	NE	NE
Gasoline	NE	NE
ASTM #3 Oil	NE	NE
SAE 20 Oil	NE	NE
Alconox®	NE	NE
Water	NE	NE

NE = No Effect
F = Failed (affected Sample)

7 Day Immersion: Immersed in reagent for 7 days.
Dip Test: Five 10 minute dips in reagent with 30 minute recovery.

Shelf Life:

1 year when stored at 70°F (21°C) and 40% to 50% R.H.

Note: All values shown are averages and should not be used for specification purposes.

Trademarks:

ASTM: American Society for Testing and Materials (U.S.A.)

Alconox® is a registered trademark of Alconox Co.

SAE: Society of Automotive Engineers (U.S.A.)

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide, Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289