



**TECHNICAL DATA SHEET**

**PLEASE REFER TO SPC300-E AND OIL412 FOR INDIVIDUAL SPECS**

<b>Order reference</b>	<b>SKO-ATK</b>
<b>Article number</b>	<b>813859</b>

<b>Date</b>	4-11-11	<b>Replaces</b>	10-13-03	<b>No. Pages</b>	1
-------------	---------	-----------------	----------	------------------	---

**Product Description:**

<b>Style</b>	Spill Kit - "Attack Pac"
<b>Item Size (each)</b>	Bag
<b>Packaging</b>	Silver Vacuum-Sealed bag. A single metal grommet is pressed into the top center of the bag, above the seal but at least 7/8" away from the top edge of the bag.
<b>Contents (each)</b>	15 SPC300-E (41cm x 51cm) Pads, 3 OIL412 (7.6 cm x 122 cm) Soc's, 1 pair of goggles, 1 pair of Nitrile gloves, 1x 6-mil disposal bag and 1 instruction sheet.
<b>Color</b>	Silver
<b>Absorbency</b>	Oil Only ( <b>Hydrophobic + Oleophilic</b> )

<b>Intended Application</b>	Emergency kits for fast response of spills
-----------------------------	--

<b>Absorbency Capacity</b>	104 l per case (saturated; medium viscosity)
----------------------------	--

**Packaging Description:**

Package configuration	Case	Pkg. Weight	18.1 kg
Items per Package	4 Packs/Case	Pkg. Dimensions	47cm x 47cm x 44cm
Container type	Carton		

**Physical Properties:**

<u>Parameter</u>	<u>SPC Test Method</u>	<u>Units</u>	<u>Nominal</u>	<u>(+/-)Tolerance</u>
Color	Visual	-----	Silver	per standard

**The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.**

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).
<b>Certification</b>	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.