

Product information sheet

BRADY B-7539 THERMAL TRANSFER PRINTABLE WHITE POLYESTER

GENERAL DESCRIPTION :

B-7539 is a 50 micron Gloss White Polyester with a removable adhesive. This is an exceptionally white opaque film with a satin surface finish.

Recommended THT ribbon on B-7539: R-4900 and R-7962

PROPERTIES:

Thickness	substrate (polyester+clear vinyl) adhesive total	0.050 mm 0.015 mm 0.065 mm
Peel adhesion (ASTM D-1000)	Stainless Steel (24 h dwell time)	18 N / 100 mm
Tack (ASTM D-2979)		370 g
Drop Shear (PSTC-7)		15 minutes
Application temperature Min. service temperature Max. service temperature		+ 5° C - 10° C +100° C
UV-resistance		No visible effect

Shelf life: 2 years if stored below 80° F (26,5° C) and 60% R.H.

Product testing, customer feedback, and history of similar products, support a customer performance expectation of at least two years from the date of receipt for this product as long as this product is stored in its original packaging in an environment below 80 degrees F and 60% RH. We are confident that our product will perform well beyond this time frame. However, it remains the responsibility of the user to assess the risk of using such product. We encourage customers to develop functional testing protocols that will qualify a product's fitness for use, in their actual applications.

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2008 Brady Worldwide, Inc., All Rights Reserved Material may not be reproduced or distributed in any form without permission.