



**TECHNICAL DATA SHEET**

|                        |                |
|------------------------|----------------|
| <b>Order reference</b> | <b>OIL1818</b> |
| <b>Article number</b>  | <b>813780</b>  |

|             |         |                 |         |                  |   |
|-------------|---------|-----------------|---------|------------------|---|
| <b>Date</b> | 6-30-06 | <b>Replaces</b> | 3-19-01 | <b>No. Pages</b> | 1 |
|-------------|---------|-----------------|---------|------------------|---|

**Product Description:**

|                         |  |
|-------------------------|--|
| <b>Style</b>            | Pillow --“Lint-Free”   |
| <b>Item Size (each)</b> | 43 cm x 48 cm x 5 cm   |
| <b>Color</b>            | White with blue logo printing  |
| <b>Composition</b>      | 100% Polypropylene   |
| <b>Structure</b>        | <u>Sorbent fill:</u> Micro-fibrous meltblown polypropylene (2-10 micron diameters)<br><u>Outer covering:</u> Spunbond polypropylene nonwoven (15-30 micron dia. fiber) |
| <b>Technology</b>       | Meltblown + Spunbond   |
| <b>Absorbency</b>       | <b>Hydrophobic</b> + Oleophilic  |

|                             |   |
|-----------------------------|---|
| <b>Intended Application</b> | Non -Linting Chemical Resistant Sorbent Pillow for Oil or Solvent Based Liquids |
|-----------------------------|---|

|                            |  |
|----------------------------|--|
| <b>Absorbency Capacity</b> | 105 l per case (saturated; medium viscosity-12.5x) |
|----------------------------|--|

**Packaging Description:**

|                       |                 |                           |                      |
|-----------------------|-----------------|---------------------------|----------------------|
| Package configuration | 1-Case          | Pkg. Weight               | 9.1 kg (7.3 kg)      |
| Items per Package     | 16-Pillows/Case | Pkg. Dimensions (approx.) | 64cm x 43cm x 53cm H |
| Container type        | Carton          |                           |                      |

**Physical Properties:**

| <u>Parameter</u>        | <u>SPC Test Method</u> | <u>Units</u> | <u>Nominal</u>       | <u>(+/-)Tolerance</u> |
|-------------------------|------------------------|--------------|----------------------|-----------------------|
| Pillow Weight           | W.I.P.                 | kg           | 0.45                 | 0.09                  |
| Absorbency** (med. oil) | SPCTM-012B             | gL/gS        | 12.5                 | 10-min.               |
| Color                   | Visual                 | -----        | White with blue logo | per standard          |

**The above properties are “nominal” values used for PROCESS CONTROL when the product is produced and/or inspected. Performance “nominals” may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.**

**\*\* The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.**

|                      |  |
|----------------------|--|
| <b>Attributes</b>    | Product will be free of foreign material contamination, rips, holes, and tears.  |
| <b>Labeling</b>      | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code).   |
| <b>Certification</b> | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |